



COATINGS TECHNOLOGY (PTY) LTD

Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911

Posbus / PO Box 1576
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

001

RETEK MASTER DECORATORS ACRYLIC FILLERCOAT

Master decorators acrylic fillercoat is a high quality coating with high hiding power, low gloss and odour and can be used on ceilings or as a first coat on interior walls

Master decorators acrylic fillercoat exhibits the following features:

- Water based, so cleaning of equipment is a feast
- Ultra matt finish
- It has superior hiding power
- It contains no harmful agents
- It has an agreeable odour on application which will disappear in a short period of time
- It is manufactured from a high quality acrylic emulsion
- Excellent adhesion
- Water based
- Only requires one coat on most surfaces
- Can easily over coated

Master decorators acrylic fillercoat can be used on the following surfaces:

- Ceilings
- As first coat on cement plastered walls

Application procedures

- Clean all surfaces from dust, oil or other contaminants
- If necessary a primer or sealer can be used depending on the nature of the substrate
- Defects can be filled with an appropriate filler
- Master decorators acrylic fillercoat can be applied by roller, brush or roller
- Stir thoroughly before use
- One coat of Master decorator's acrylic fillercoat should be sufficient on most surfaces.
- As this material is very easy to apply, care should be taken not to overspread
- After application, the equipment and any spillage can be cleaned with water and soap followed by thorough rinsing with clean water

Maintenance of master decorator's acrylic fillercoat painted surfaces

Surfaces that have been coated with Master decorator's acrylic fillercoat are very easy to maintain-Just wash with an ordinary household cleaner or soft soap by using a soft cloth and it will be restored to its original pristine condition

Product information

Master decorators acrylic fillercoat is supplied in 1,5 and 20 litre containers

A wide range of colours is available

It has a spreading rate of 10-12 Metres² per litre (depending on colour)