



## **COATINGS TECHNOLOGY (PTY) LTD**

Re-Tek Power House  
Hv/Cnr Jenner & Lister Str/St  
Vanderbijlpark, 1911

Posbus / PO Box 1576  
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146  
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

---

0045

### **PRODUCT DATA SHEET** (Replace Feb 02 with Nov 09)

## **RETEK FLOOR EPOXY (ECONOMICAL)**

### **Description**

Retek Floor epoxy systems are designed to provide protection, easy to clean and maintain to new and existing concrete floors.

We offer a variety of colours, which comes in pre-measured kit form.

### **Recommended uses**

This is a low cost flooring system which can be applied over your existing concrete, ceramic or quarry tile, wood and metal. It can also be installed on vertical surfaces such as steps, walls.

- House floors
- Warehouse
- Bathroom
- Laboratories
- Garage
- Walk ways
- Workshops
- Locker and tea room
- Store room
- Food process areas

### **Application**

- All surfaces should be cleaned from all loose debris, dust, oils, grease, animal fats etc.
- Mix part A separately, then add Part B and mix thoroughly
- Use Epoxy roller, brush only recommended for corners and touch-up.

**Coverage**

± 3m<sup>2</sup>/per kg at 80 microns dry film thickness.

**Drying Times**

24 Hours at ± 20°C.

**Shipping weight**

- Part A and B - 5kg
- Retek Thinners 30 – 5kg