



COATINGS TECHNOLOGY (PTY) LTD

Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911

Posbus / PO Box 1576
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

0065

PRODUCT DATA SHEET (Nov 2009) **NONCONDUCTIVE FLOOR EPOXY**

Description

Retek Nonconductive floor epoxy is an electrostatic discharge system. The electrical properties obtainable through the use of this system has a power factor below 0, 3 even at 100°C.

Recommended uses

This system can be applied on floor and wall.

- Control room
- Substations
- Industrial plants
- Encapsulation Impregnation of electrical equipment
- Computer rooms
- Laboratories

Application

- All surfaces should be cleaned from all loose debris, dust, oils and grease.
- Mix Part A separately, then add Part B and mix thoroughly.
- Use Epoxy roller.
- Brush only recommended for corners and touch-up.

Coverage

± 3m²/per kg at 80 microns dry film thickness.

Drying time

24 hours at ± 20°C

Shipping weight

Part A + B – 5kg
Retek Thinners 30 – 5kg